

Technical Data Sheet nr: F 7.2- 24, Rev 2

MULTIGRAD ENGINE OIL
15W40 Universal -F , Agri Universal 15W40 -F, 15w40 Truck -F, Agri Premium 15w40 E9
Brand Fatcom / e-oil

EN- 10W40 Premium-F is a high quality, multigrade, semi-synthetic oil, recommended for lubricating engines for cars, trucks, buses, agricultural machinery, and industrial equipment where this type of lubricant is recommended by the manufacturer. Provides good protection against wear, oxidation, corrosion. **The oil can be mixed with other oils with similar characteristics.**

Properties: good anti-wear, anti-rust, anti-corrosion and viscosity index properties

Characteristics	Test methods	15W40 Universal - F	Agri Universal 15W40 -F	15W40 Truck -F	Agri Premium 15w40 E9
Clasa de vascozitate		SAE 15W40	SAE 15W40	SAE 15W40	SAE 15W40
Specificatii		SF/CC	CI -4	CI -4	CK-4, E9
Kinematic viscosity at 40 ° C,	SR ISO 3104 ASTM D 445 ASTM D 7042	12,5-16,3	12,5-16,3	12,5-16,3	12,5-16,3
Kinematic viscosity at 100 ° C,	STAS 55 ASTM D 2270 ASTM D 7042	135	135	135	135
Flow point, max	STAS 6170 ASTM D 97	-30	-30	-30	-30
Flash point COC, min.	STAS 7329 ASTM D 92	210	210	210	210
Density at 20 ° C, max	SR EN ISO 3675/C91 ASTM D 1298 ASTM D 7042	0,9	0,9	0.9	0.9

Shelf life, when stored is 3 years from the date of manufacture, kept in the original packaging, protected from sunlight, heat and cold. Recommended storage temperature between 5 ° C and 25 ° C.

Date: 2022.06.29

Form Code: F 7.2- 24 Rev 2.