

Technical Data Sheet nr: F 7,2- 43 Rev 0

 2T-F
 Brand: Fatcom/e-oil

- Mixing oil for 2-stroke engines,
- Good anti-corrosion, anti-rust properties, oxidation stability, smoke reduction.
- APPLICATIONS: it is a mixed oil, recommended for lubricating 2-stroke engines that equip cars, motorcycles, mopeds, gardening equipment, agricultural machinery, as well as other equipment, where this type of lubricant is recommended by the manufacturer.
- Performance level: API TA

Characteristics	Unit	Test methods	2T -F
Kinematic viscosity at 40 ° C,	mm ² /s (cSt)	SR EN ISO 3104/AC ASTM D 445	32 - 100
Kinematic viscosity at 100 ° C,	mm ² /s (cSt)	SR EN ISO 3104/AC ASTM D 445	5 - 11
Viscosity index, min.		ASTM D 2270	90
Flow point, max	°C	ASTM D 97	-15
Flash point COC, min.	°C	ASTM D 92	210
Density at 20 ° C, max	Kg/m ³	SR EN ISO 3675 ASTM D 1298	900

Shelf life, when stored is 3 years from the date of manufacture, kept in the original packaging, protected from sunlight, heat and cold. Recommended storage temperature between 5 ° C and 25 ° C.