

Technical Data Sheet nr: F 7,2- 45 Rev 1

 4T 10W40-F si 4T 10w30 Garden -F
 Brand: Fatcom/e-oil

- 4T 10w40 - Semi-synthetic oil, multigrade for engine, 4T 10w30 Garden -F - Synthetic oil for small agricultural machinery
- Good anti-corrosion, anti-rust properties, oxidation and shear stability, high viscosity index.
- APPLICATIONS: 4T 10w40 - is a semi-synthetic, multigrade oil, recommended for lubricating engines that equip motorcycles, cars, trucks, buses, as well as industrial equipment, where this type of lubricant is recommended by the manufacturer.
4T 10W30 Garden-F- is a synthetic oil gardening equipment, agricultural machinery, where this type of lubricant is recommended by the manufacturer.
- Performance level: 4T 10w40 - API SL, 4T 10w30 Garden-F - SL/CF

Characteristics	Unit	Test methods	4T 10w40-F	4T 10W30 Garden -F
Kinematic viscosity at 40 ° C,	mm ² / s (cSt)	SR EN ISO 3104/AC ASTM D 445	85 - 130	-
Kinematic viscosity at 100 ° C,	mm ² / s (cSt)	SR EN ISO 3104/AC ASTM D 445	12,5 - 16,3	14-15
Viscosity index, min.		ASTM D 2270	140	145
Flow point, max	°C	ASTM D 97	-25	-27
Flash point COC, min.	°C	ASTM D 92	210	212
Density at 20 ° C, max	Kg/m ³	SR EN ISO 3675 ASTM D 1298	900	

Shelf life, when stored is 3 years from the date of manufacture, kept in the original packaging, protected from sunlight, heat and cold. Recommended storage temperature between 5 ° C and 25 ° C.