

Technical Data Sheet nr: F 7,2- 55 Rev 0

Agri STOU 10W30-F
Brand: Fatcom/e-oil

- Semi-synthetic, multifunctional, multigrade engine oil, transmission and tractor hydraulic system (Super Tractor Oil Universal)
- Good anti-corrosion, anti-rust properties, oxidation and shear stability, high viscosity index.
- APPLICATIONS: is a semi-synthetic, multigrade, multifunctional oil, recommended for lubricating engines, transmissions and hydraulic systems that equip tractors and agricultural machinery, as well as other equipment, where this type of lubricant is recommended by the manufacturer.
- Performance level: API CG-4/SF, ACEA E3, API GL-4,

Characteristics	Unit	Test methods	Agri STOU 10w30-F
Kinematic viscosity at 40 ° C,	mm ² /s (cSt)	SR EN ISO 3104/AC ASTM D 445	55 - 100
Kinematic viscosity at 100 ° C,	mm ² /s (cSt)	SR EN ISO 3104/AC ASTM D 445	9,3 - 12,5
Viscosity index, min.		ASTM D 2270	140
Flow point, max	°C	ASTM D 97	-25
Flash point COC, min.	°C	ASTM D 92	200
Density at 20 ° C, max	Kg/m ³	SR EN ISO 3675 ASTM D 1298	900

Shelf life, when stored is 3 years from the date of manufacture, kept in the original packaging, protected from sunlight, heat and cold. Recommended storage temperature between 5 ° C and 25 ° C.