

Technical Data Sheet nr: F 7,2- 12 Rev 1

 M30S2-F, M40S2-F
 Brand: Fatcom/e-oil

- Monograde engine oil,
- Good anti-corrosion, anti-rust properties, oxidation and shear stability, high viscosity index.
- APPLICATIONS: it is a monograde oil, recommended for lubricating engines that equip cars, trucks, buses, agricultural machinery, as well as industrial equipment, where this type of lubricant is recommended by the manufacturer. Recommended for use when the ambient temperature exceeds 5 ° C.
- Nivel de performanță: API SC/CC

Characteristics	Unit	Test methods	M30S2-F	M40S2-F
Kinematic viscosity at 40 ° C,	mm ² /s (cSt)	SR EN ISO 3104/AC ASTM D 445	80 - 125	125 - 190
Kinematic viscosity at 100 ° C,	mm ² /s (cSt)	SR EN ISO 3104/AC ASTM D 445	9,3 - 12,5	12,5 - 16,3
Viscosity index, min.		ASTM D 2270	90	90
Flow point, max	°C	ASTM D 97	-10	-10
Flash point COC, min.	°C	ASTM D 92	210	220
Density at 20 ° C, max	Kg/m ³	SR EN ISO 3675 ASTM D 1298	900	910

Shelf life, when stored is 3 years from the date of manufacture, kept in the original packaging, protected from sunlight, heat and cold. Recommended storage temperature between 5 ° C and 25 ° C.