

Technical Data Sheet nr: F 7,2- 41 Rev 0

**ATF Universal-F**  
**Brand: Fatcom/e-oil**

- e-oil ATF Universal is an automatic transmission fluid recommended for use in automatic transmissions, power steering, hydraulic equipment, agricultural or industrial machinery, if this type of lubricant is recommended by the manufacturer.
- Good anti-corrosion, anti-rust properties, oxidation and shear stability, high viscosity index, resistance to high pressures
- APPLICATIONS: is an automatic transmission fluid, recommended for use in automatic transmissions, power steering, hydraulic equipment, agricultural or industrial machinery, if this type of lubricant is recommended by the manufacturer. It has a good performance at low temperatures.
- Performance level: GM Type A Suffix A

Characteristics	Unit	Test methods	ATF Universal-F
Kinematic viscosity at 40 ° C,	mm <sup>2</sup> /s (cSt )	SR EN ISO 3104/AC ASTM D 445	32 - 68
Kinematic viscosity at 100 ° C,	mm <sup>2</sup> /s (cSt )	SR EN ISO 3104/AC ASTM D 445	5 - 9
Viscosity index, min.		ASTM D 2270	90
Flow point, max	°C	ASTM D 97	-25
Flash point COC, min.	°C	ASTM D 92	200
Density at 20 ° C, max	Kg/m <sup>3</sup>	SR EN ISO 3675 ASTM D 1298	900

Shelf life, when stored is 3 years from the date of manufacture, kept in the original packaging, protected from sunlight, heat and cold. Recommended storage temperature between 5 ° C and 25 ° C.