

Technical Data Sheet nr: F 7,2- 38 Rev 1

**ATF II-F, ATF III-F**  
**Brand: Fatcom/e-oil**

- Synthetic oil, for automatic transmissions (ATF III-F), oil for automatic transmissions (ATF II-F)
- Good anticorrosive properties, anti-rust, stability to oxidation and shear, high viscosity index, resistance to high pressures
- APPLICATIONS: intended for the lubrication of automatic gearboxes, power steering, as well as any other equipment where the manufacturer recommends the use of an oil with these characteristics. They have a very good performance at low temperatures. Excellent behavior as a hydraulic fluid in hydraulic systems where a fluid with an increased viscosity index is recommended.
- Performance level:
  - o ATF II-F: GM Dexron II-D,
  - o ATF III-F: GM Dexron III-H.

Characteristics	Unit	Test methods	ATF II-F	ATF III-F
Kinematic viscosity at 40 ° C,	mm <sup>2</sup> /s (cSt )	SR EN ISO 3104/AC ASTM D 445	30 - 50	30 - 50
Kinematic viscosity at 100 ° C,	mm <sup>2</sup> /s (cSt )	SR EN ISO 3104/AC ASTM D 445	6 – 8	6 – 8
Viscosity index, min.		ASTM D 2270	150	170
Flow point, max	°C	ASTM D 97	-35	-40
Flash point COC, min.	°C	ASTM D 92	200	200
Density at 20 ° C, max	Kg/m <sup>3</sup>	SR EN ISO 3675 ASTM D 1298	880	880
Color			red	red

Shelf life, when stored is 3 years from the date of manufacture, kept in the original packaging, protected from sunlight, heat and cold. Recommended storage temperature between 5 ° C and 25 ° C.