

Technical Data Sheet nr: F 7,2- 57 Rev 0

Agri UTTO 80W-F
Brand: Fatcom/e-oil

- Universal transmission oil and tractor hydraulic system
- Good anti-corrosion, anti-rust properties, oxidation and shear stability, high viscosity index, resistance to high pressures
- APPLICATIONS: intended for agricultural machinery, land improvement, industrial equipment and any other machinery where the manufacturer recommends the use of an oil with these characteristics. It has a good performance at low temperatures.
- Performance level: API GL-4, Caterpillar TO-2, John Deere JDM J20C

Characteristics	Unit	Test methods	UTTO 80W-F
Kinematic viscosity at 40 ° C,	mm ² /s (cSt)	SR EN ISO 3104/AC ASTM D 445	40 - 80
Kinematic viscosity at 100 ° C,	mm ² /s (cSt)	SR EN ISO 3104/AC ASTM D 445	7 - 11
Viscosity index, min.		ASTM D 2270	130
Flow point, max	°C	ASTM D 97	-30
Flash point COC, min.	°C	ASTM D 92	200
Density at 20 ° C, max	Kg/m ³	SR EN ISO 3675 ASTM D 1298	900

Shelf life, when stored is 3 years from the date of manufacture, kept in the original packaging, protected from sunlight, heat and cold. Recommended storage temperature between 5 ° C and 25 ° C.