

Technical Data Sheet nr: F 7,2- 14 Rev 1

T75 EP1-F
Brand: Fatcom/e-oil

- Transmission oil, monograde
- Good anti-corrosion, anti-rust properties, oxidation and shear stability, high viscosity index, resistance to high pressures
- APPLICATIONS: The oil is used for lubricating the transmissions through the gears of the tractors and as a hydraulic fluid, according to the provisions of the technical book or the operating instructions of the tractors
- Performance level: : API GL2

Characteristics	Unit	Test methods	T75 EP1-F
Kinematic viscosity at 40 ° C,	mm ² /s (cSt)	SR EN ISO 3104/AC ASTM D 445	32 - 68
Kinematic viscosity at 100 ° C,	mm ² /s (cSt)	SR EN ISO 3104/AC ASTM D 445	5 - 9
Viscosity index, min.		ASTM D 2270	90
Flow point, max	°C	ASTM D 97	-25
Flash point COC, min.	°C	ASTM D 92	200
Density at 20 ° C, max	Kg/m ³	SR EN ISO 3675 ASTM D 1298	900

Shelf life, when stored is 3 years from the date of manufacture, kept in the original packaging, protected from sunlight, heat and cold. Recommended storage temperature between 5 ° C and 25 ° C.