

Technical Data Sheet nr: F 7,2- 15 Rev 1

T90 EP2-F
Brand: Fatcom/e-oil

- Ulei de transmisie, monograd
- Good anti-corrosion, anti-rust properties, oxidation and shear stability, high viscosity index, resistance to high pressures
- APPLICATIONS: used for lubricating transmissions through gears: gearboxes, reducers, differentials, steering boxes, according to the technical book and operating instructions of the vehicle
- Performance level: : API GL2

Characteristics	Unit	Test methods	T90 EP2-F
Kinematic viscosity at 40 ° C,	mm ² /s (cSt)	SR EN ISO 3104/AC ASTM D 445	135 - 220
Kinematic viscosity at 100 ° C,	mm ² /s (cSt)	SR EN ISO 3104/AC ASTM D 445	13 - 18
Viscosity index, min.		ASTM D 2270	90
Flow point, max	°C	ASTM D 97	-20
Flash point COC, min.	°C	ASTM D 92	220
Density at 20 ° C, max	Kg/m ³	SR EN ISO 3675 ASTM D 1298	910

Shelf life, when stored is 3 years from the date of manufacture, kept in the original packaging, protected from sunlight, heat and cold. Recommended storage temperature between 5 ° C and 25 ° C.